

Claims

- [c1] What is claimed is:
- 1.A chip-packaging with bonding options connected to a package substrate, comprising:
a package substrate;
a chip mounted on the package substrate, the chip comprising a plurality of bonding pads, one of the bonding pads being connected to the package substrate; and
a lead frame connected to one of the bonding pads.
 - [c2] 2.The chip-packaging in the claim 1, wherein the package substrate is connected to a high voltage or a low voltage.
 - [c3] 3.The chip-packaging in the claim 2, wherein the high voltage is a power supply and the low voltage is ground.
 - [c4] 4.The chip-packaging in the claim 1, wherein the lead frame is connected to a pin of the chip.
 - [c5] 5.The chip-packaging in the claim 4, wherein the pin is connected to a high voltage, a low voltage, or an input/output signal.
 - [c6] 6.A method of packaging a chip having a bonding option

connected to a package substrate, comprising:
providing the package substrate;
mounting the chip on the package substrate, the chip
comprising a plurality of bonding pads;
connecting one of the bonding pads to the package sub-
strate; and
connecting one of the bonding pads to a lead frame.

[c7] 7.The method of packaging a chip in claim 6 further
comprising connecting the package substrate to a high
voltage or a low voltage.

[c8] 8.The method of packaging a chip in claim 7, wherein
the high voltage is a power supply of the chip, and the
low voltage is ground of the chip.

[c9] 9.The method of packaging a chip in claim 6 further
comprising connecting the lead frame to one pin of the
chip.

[c10] 10.The method of packaging a chip in claim 9 further
comprising connecting the pin to a high voltage, a low
voltage, or an input/output signal.